

Tarkett Living 30-55

Click Luxury Vinyl Tiles

The Exclusive
Collection

Scratched Cement Grey

280063010

 **Tarkett**



Cool Oak Classic

280062001

 **Tarkett**



Cool Oak Light Beige

280062002



Primary Oak Beige

280062003

 **Tarkett**



Primary Oak Natural

280062004

 **Tarkett**



Primary Oak Light Brown

280062005


 **Tarkett**



Primary Oak Light Grey

280062006

 **Tarkett**



Tribe Oak Light Natural

280062007

 **Tarkett**



Tribe Oak Grey

280062008


 **Tarkett**



Tribe Oak Mocha

280062009

 **Tarkett**



Tarkett Living 30-55

Classification	Norm	Tarkett Value
Domestic classification	EN ISO 10874	23 Heavy
Commercial classification	EN ISO 10874	31 Moderate
Technical characteristics	Norm	Tarkett Value
Total thickness	EN ISO 24346	5 mm
Wear layer thickness	EN ISO 24340	0.30 mm
Total weight	EN ISO 23997	8350 g/m ²
Binder content	EN ISO 10582	Type I
Surface treatment		PU Mat
Bevelled edges		4 sides micro bevels
Installation method		Click
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 14041	0132-0100-DoP-2025-05
Technical performance	Norm	Tarkett Value
Dimensional stability	EN ISO 23999	≤ 0.15 %
Curl resultant to heat	EN ISO 23999	≤ 1 1 mm
Reaction to fire	EN 13501-1	Bfl-s1
Residual indentation	EN ISO 24343-1	≤ 0.10 mm
Furniture leg	EN ISO 16581	No damage
Impact sound reduction – ΔLw	EN ISO 717-2	19 dB
Reduction of in-room impact noise	NF S31-074	Class C (≤ 85 dB)
Thermal resistance	EN ISO 10456	0.05 m ² •K/W
Light fastness	EN ISO 105-B02	≥ 6
Chemical resistance	EN ISO 26987	Good resistance
Slip resistance	EN 13893	Class DS (μ ≥ 0.30)
Peeling resistance	EN ISO 24345	≥ 50 N / 50 mm
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Sustainability performance	Norm	Tarkett Value
Recyclability through ReStart®		Offcuts / Post-use – Contact Tarkett for more information
Recycled content	ISO 14021	20 %
Total VOC emissions (after 28 days)	EN 16516	Platinum (≤ 10 μg/m ³)
Dimensions and designs		Tarkett Value
Plank		Plank 1220 × 181mm – 11 planks = 2.44 m ² /box – 48 boxes/pallet
Tile		Tile 300 × 600 mm – 13 tiles = 2.34 m ² /box – 48 boxes/pallet
Number of designs available		10



The above information is subject to modification for the benefit of further improvement (24/04/2025). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.

